

Product Brochure

Matchbox 50W Ka-Wideband BUC

WBAN-050G01-0005

Field-Proven Performance

Gilat's Matchbox 50W Ka-Wideband Deck Block Up Converter (BUC) is the next generation of the world's most widely deployed solid state amplifier built at this power level. Gilat enables a full 25 Watts of linear power into the feed with a rugged unit that can be mounted directly onto the feed arm of medium aperture antennas.

The 50W Ka-Wideband BUC is designed to operate in the most extreme environments, and offers field-proven reliability to support the most demanding satellite communications applications. The 50W Ka-Wideband BUC includes L-band to Ka-band upconversion, serial / Ethernet monitor and control, adjustable attenuation and forward and reverse output power monitoring.

Weighing just 13.2 pounds, this compact unit provides the same power as its previous generation but within 52% less volume and a 60% reduction in weight.

Features

- 25W Linear Power for Higher Data Rate Capability
- Rugged; Mounts on Feed Arm for Simple Integration
- High Reliability
- Supports Multiple Commercial Ka Bands
- 52% decrease in volume
- 60% decrease in weight

Gilat Advantages

What sets Gilat products apart from traditional amplifier solutions is the innovative Spatial advantEdge™ technology. This unique patented technology allows generation of higher output power in lighter, more compact product packages that use less energy and are more reliable. Gilat products are biased for Class AB operation, drawing less power when backed off to help save valuable energy resources. They generate less heat, ensuring higher Mean Time Between Failures (MTBF) for greater reliability and lower life cycle maintenance costs.

Benefits

- Operates on GEO, MEO, and LEO Ka-Band Satellites
- Field proven reliability and efficiency
- Higher output power with less energy usage
- Reduced life cycle maintenance costs



Matchbox 50W Ka-Wideband BUC

Technical Specifications

RF Specifications

Transmit Frequency:

27.5 – 28.5 GHz
28.25 – 29.25 GHz
29.0 – 30.0 GHz

IF Frequency:

950 MHz – 1950 MHz

Frequency Reference

(10 MHz on IF): 0 dBm ± 5 dB

Small Signal Gain:

77 dB (nominal)

Gain Adjustment:

30 dB in 0.25 dB steps (nominal)

Gain Variation:

- Over frequency at fixed temp:
4 dB p-p (max) over 1000 MHz
- Over temp at fixed frequency:
3 dB p-p (max) over operating range

Saturated Output Power:

47 dBm (nominal)

Linear Output Power, defined by MIL-STD-188-164:

- Multi-carrier (Intermodulation):
44 dBm
- Single-carrier (Spectral Regrowth): 44 dBm

Phase Noise:

- 10 Hz: –33 dBc/Hz
- 100 Hz: –63 dBc/Hz
- 1 kHz: –73 dBc/Hz
- 10 kHz: –83 dBc/Hz
- 100 kHz: –93 dBc/Hz
- 1 MHz: –103 dBc/Hz

Noise Power Density Transmit:

–76 dBm/Hz (maximum)

Transmit:

–76 dBm/Hz (maximum)

Noise Power Density Receive:

–156 dBm/Hz

Output Spurious: –60 dBc

Interfaces

IF Input Connector:

Type N Female

IF Input Impedance: 50 Ohms**IF Input VSWR:**

1.67:1 maximum

RF Output Connector:

WR-28

RF Output VSWR:

1.25:1 maximum

DC Connector:

ITT Cannon

CIR030FP – 20A – 9P – F80 – 20

M&C Connector:

Amphenol #360011

M&C Protocol:

Serial RS-485/RS-232 (SA-bus)
or Ethernet (WebGUI, SNMP, UDP,
or TCP/IP)

Power

DC Power:

20 – 56 VDC

DC Power Draw:

360W maximum (at Linear
Output Power)

Physical

Size:

12.0" L x 7.0" W x 6.5" H
(30.5 x 17.8 x 16.5 cm)

Weight: 13.2 lbs (6 kg)**Operating Temperature****(Ambient Air):**

–40°F to +140°F
(–40°C to +60°C)

Relative Humidity:

100% Condensing

Shock & Vibration:

MIL-STD-810E, method 514-4

Altitude:

10,000 ft above sea level
(operating)

Base Model

WBAN-050G01-0005

*Requires selection of appropriate IDU part number

About Gilat Wavestream

Gilat Wavestream sets the standard in the design and manufacture of next generation high power solid state amplifiers. Wavestream's Family of Ka, Ku and X-band Solid State Power Amplifiers (SSPAs), Block Upconverters (BUCs) and transceivers provide systems integrators with field-proven, high performance solutions designed for ground mobile and fixed, gateway and airborne satellite communication systems worldwide.

These items are subject to the Export Administration Regulations (EAR), 15 C.F.R. Parts 730-774, and may not be exported or transferred to any non-U.S. person, except as authorized by the U. S. Department of Commerce.

Contact Us

545 West Terrace Drive
San Dimas, California 91773 USA
T. +1 909 599 9080
F. +1 909 599 9082
www.wavestream.com
sales@wavestream.com

All registered trademarks are the property of their respective companies. This brochure is being provided for informational purposes only. The details contained in this document, including product and feature specifications, are subject to change without notice and shall not bind Wavestream to a specific product or set of features related thereto.

